



Ceramic Fiber Enterprises

CFE Module Armor 2600 & 3000HH (Trowelable)



Applications

- ❖ Introducing “Module Armor 2600 & 3000HH” - the ultimate solution for scaling and protecting furnaces operating at extreme temperatures. Crafted with precision and innovation, Module Armor 2600 & 3000HH is a cutting-edge ceramic fiber module coating designed to withstand the hottest conditions.
- ❖ At high temperatures, forms a resilient barrier, scaling your furnace with efficiency. Its advanced formulation ensures exceptional thermal insulation, preventing heat loss and maintaining energy efficiency.



Technical Data

- ❖ Color: White to Off White
- ❖ Temperature Grades: CFE Module Armor 2600: 2600°F (1427°C)
CFE Module Armor 3000HH: 3000°F (1649°C)
- ❖ Recommend Operating Temperature: CFE 2600: 2450°F (1343°C)
CFE 3000HH: 2700°F (1482°C)
- ❖ 6 Month shelf life from Manuf. Date.
- ❖ Packaged in 1 & 5 gal pails

We're on



Scott Marker
(574)-584-4839
sam@cfeworld.com

Brett Lugo
(219)-255-8099
brettl@cfeworld.com

Richard Berry
(765)-720-8975
Richard@cfeworld.com

4455 W 300 N Crawfordsville, IN 47933